## NSN 5306-01-142-3217

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-142-3217
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.433 inches and 1.483 inches
Fastener Length:
Between 3.943 inches and 3.973 inches
Head Style:
Dished hexagon
Head Height:
Between 0.562 inches and 0.577 inches
Width Between Flats:
Between 1.614 inches and 1.627 inches
Grip Diameter:
Between 1.1225 inches and 1.1240 inches
Thread Diameter:
1.125 inches
Grip Length:
Between 2.490 inches and 2.510 inches
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6618 professional/industrial association standard

N/a

Shelf Life:

## NSN 5306-01-142-3217

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.