NSN 5306-01-142-4392

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-142-4392 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.589 inches and 0.639 inches **Fastener Length:** Between 1.599 inches and 1.629 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Shoulder Diameter:** 0.4052 inches first shoulder and 0.4057 inches first shoulder **Shoulder Length:** 0.990 inches first shoulder and 1.010 inches first shoulder **Head Minor Diameter:** 0.448 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-142-4392 Shoulder Bolt - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

Demilitarization:

No

Fiig:

A003b0