## NSN 5306-01-142-4393

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-142-4393 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.742 inches and 0.792 inches **Fastener Length:** Between 4.564 inches and 4.594 inches **Head Style:** Spline extended washer **Head Height:** Between 0.440 inches and 0.460 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches **Extended Washer Thickness:** Between 0.062 inches and 0.082 inches **Shoulder Diameter:** 0.5302 inches first shoulder and 0.5307 inches first shoulder **Shoulder Length:** 3.802 inches first shoulder and 3.822 inches first shoulder **Head Minor Diameter:** 0.644 inches **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## **NSN 5306-01-142-4393** Shoulder Bolt - Page 2 of 2



		eas	

Demilitarization:

No

Fiig:

A003b0