## NSN 5306-01-142-7171

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-142-7171

View Online at https://aerobasegroup.com/nsn/5306-01-142-71						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.742 inches and 0.792 inches						
Fastener Length:						
Between 2.064 inches and 2.094 inches						
Head Style:						
Spline extended washer						
Head Height:						
Between 0.440 inches and 0.460 inches						
Width Between Flats:						
Between 0.644 inches and 0.651 inches						
Extended Washer Diameter:						
Between 0.922 inches and 0.932 inches						
Extended Washer Thickness:						
Between 0.062 inches and 0.082 inches						
Shoulder Diameter:						
0.5302 inches first shoulder and 0.5307 inches first shoulder						
Shoulder Length:						
1.302 inches first shoulder and 1.322 inches first shoulder						
Thread Diameter:						
0.500 inches						
Thready Qty Per Inch (tpi):						
20						
Min. Tensile Strength (psi):						
220000 pounds per square inch						
Shoulder Shape:						
Round first shoulder						
Material:						
Steel comp xm-13						
Material Specification:						
Ams5629 assn standard single material response						
Surface Treatment:						
Passivate						
Surface Treatment Specification:						
Qq-p-35 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Shelf Life:						
NI/o						

N/a

## **NSN 5306-01-142-7171** Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A003b0