

View Online at <https://aerobasegroup.com/nsn/5306-01-142-9356>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.526 inches and 0.576 inches

Fastener Length:

Between 1.661 inches and 1.691 inches

Head Style:

Spline extended washer

Head Height:

Between 0.302 inches and 0.322 inches

Width Between Flats:

Between 0.383 inches and 0.389 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

Between 0.035 inches and 0.055 inches

Shoulder Diameter:

0.3427 inches first shoulder and 0.3432 inches first shoulder

Shoulder Length:

1.115 inches first shoulder and 1.135 inches first shoulder

Hole Diameter:

Between 0.050 inches and 0.060 inches

Thread Diameter:

0.312 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Spline

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488, type 2, cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.