

View Online at <https://aerobasegroup.com/nsn/5306-01-142-9363>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.589 inches and 0.639 inches

**Fastener Length:**

Between 1.599 inches and 1.629 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.327 inches and 0.347 inches

**Width Between Flats:**

Between 0.448 inches and 0.455 inches

**Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Shoulder Diameter:**

0.3896 inches first shoulder and 0.3901 inches first shoulder

**Shoulder Length:**

0.990 inches first shoulder and 1.010 inches first shoulder

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Mil-c-83488, type 2, cl 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.