

View Online at <https://aerobasegroup.com/nsn/5306-01-142-9376>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.441 inches and 0.508 inches

Fastener Length:

Between 6.691 inches and 6.748 inches

Head Style:

Double hexagon

Head Height:

Between 0.177 inches and 0.197 inches

Width Between Flats:

0.502 inches

Shoulder Diameter:

0.3271 inches first shoulder and 0.3276 inches first shoulder

Shoulder Length:

6.240 inches first shoulder and 6.260 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

6.567 inches first hole and 6.634 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0