## NSN 5306-01-143-0576

Shoulder Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-143-0576



### **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.374 inches and 0.424 inches Fastener Length: Between 0.696 inches and 0.726 inches **Head Style:** Spline extended washer **Head Height:** Between 0.195 inches and 0.215 inches **Extended Washer Diameter:** Between 0.349 inches and 0.359 inches **Extended Washer Thickness:** Between 0.017 inches and 0.037 inches **Shoulder Diameter:** 0.2177 inches first shoulder and 0.2182 inches first shoulder Shoulder Length: 0.302 inches first shoulder and 0.322 inches first shoulder Head Minor Diameter: Between 0.253 inches and 0.259 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Shoulder Shape: Round first shoulder Material:

Steel comp xm-13

#### **Material Specification:**

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-143-0576

Shoulder Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

