

View Online at <https://aerobasegroup.com/nsn/5306-01-143-0578>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.305 inches and 0.372 inches

Fastener Length:

Between 1.127 inches and 1.174 inches

Head Style:

Double hexagon

Head Height:

Between 0.130 inches and 0.150 inches

Width Between Flats:

0.376 inches

Shoulder Diameter:

0.2021 inches first shoulder and 0.2026 inches first shoulder

Shoulder Length:

0.802 inches first shoulder and 0.822 inches first shoulder

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.075 inches first hole

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.006 inches first hole and 1.063 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0