

View Online at <https://aerobasegroup.com/nsn/5306-01-143-0580>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.573 inches and 0.640 inches

**Fastener Length:**

Between 4.551 inches and 4.598 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.247 inches and 0.267 inches

**Width Between Flats:**

0.690 inches

**Shoulder Diameter:**

0.4521 inches first shoulder and 0.4526 inches first shoulder

**Shoulder Length:**

3.958 inches first shoulder and 3.978 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.423 inches first hole and 4.480 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0