

View Online at <https://aerobasegroup.com/nsn/5306-01-143-0589>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.443 inches and 0.493 inches

Fastener Length:

Between 1.140 inches and 1.170 inches

Head Style:

Spline extended washer

Head Height:

Between 0.240 inches and 0.260 inches

Extended Washer Diameter:

Between 0.460 inches and 0.470 inches

Extended Washer Thickness:

Between 0.035 inches and 0.055 inches

Shoulder Diameter:

0.2647 inches first shoulder and 0.2651 inches first shoulder

Shoulder Length:

0.677 inches first shoulder and 0.697 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Head Minor Diameter:

Between 0.318 inches and 0.324 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.948 inches first hole and 0.988 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0