NSN 5306-01-143-6510

Shoulder Bolt - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5306-01-143-6510



3a **Thread Direction: Right-hand Thread Length:** Between 0.824 inches and 0.874 inches Fastener Length: Between 4.896 inches and 4.926 inches **Head Style:** Spline extended washer **Head Height:** Between 0.495 inches and 0.515 inches **Extended Washer Diameter:** Between 1.037 inches and 1.047 inches **Extended Washer Thickness:** Between 0.071 inches and 0.091 inches **Shoulder Diameter:** 0.5922 inches first shoulder and 0.5927 inches first shoulder Shoulder Length: 4.052 inches first shoulder and 4.072 inches first shoulder Head Minor Diameter: Between 0.711 inches and 0.717 inches **Thread Diameter:** 0.562 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Shoulder Shape: Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-143-6510

Shoulder Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

