

View Online at <https://aerobasegroup.com/nsn/5306-01-144-2193>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.680 inches and 0.730 inches

Fastener Length:

Between 2.565 inches and 2.595 inches

Head Style:

Spline extended washer

Head Height:

Between 0.383 inches and 0.403 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.053 inches and 0.073 inches

Shoulder Diameter:

0.4677 inches first shoulder and 0.4682 inches first shoulder

Shoulder Length:

1.865 inches first shoulder and 1.885 inches first shoulder

Hole Diameter:

Between 0.050 inches and 0.060 inches

Head Minor Diameter:

Between 0.514 inches and 0.521 inches

Thread Diameter:

0.437 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Spline

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0