NSN 5306-01-144-3088

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-144-3088

| View Online at https://aerobasegroup.com/nsn/5306-01-144-3088 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.437 inches and 0.516 inches |
| Fastener Length: |
| Between 2.953 inches and 3.000 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.203 inches and 0.235 inches |
| Width Between Flats: |
| Between 0.615 inches and 0.627 inches |
| Grip Diameter: |
| Between 0.4358 inches and 0.4367 inches |
| Thread Diameter: |
| 0.437 inches |
| Grip Length: |
| Between 2.484 inches and 2.516 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Surface Finish: |
| 32.0 microinches grip |
| Product Name: |
| Navy special project |
| Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf Specification Data: |
| 80205-nas464 professional/industrial association standard |
| Shelf Life: |
| Olicii Elic. |

N/a

NSN 5306-01-144-3088

Shear Bolt - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0