## NSN 5306-01-144-5583

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-144-5583

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.870 inches and 0.920 inches **Fastener Length:** Between 5.255 inches and 5.285 inches **Head Style:** Dished hexagon **Head Height:** Between 0.500 inches and 0.515 inches Width Between Flats: Between 1.427 inches and 1.440 inches **Grip Diameter:** Between 0.9980 inches and 0.9990 inches **Thread Diameter:** 1.000 inches **Grip Length:** Between 4.365 inches and 4.385 inches Thready Qty Per Inch (tpi): 12 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6316 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-01-144-5583

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0