

View Online at <https://aerobasegroup.com/nsn/5306-01-144-6065>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.050 inches

**Fastener Length:**

5.140 inches

**Head Style:**

Hexagon

**Head Height:**

0.625 inches

**Width Between Flats:**

Between 1.801 inches and 1.815 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches all holes and 0.151 inches all holes

**Thread Diameter:**

1.250 inches

**Thready Qty Per Inch (tpi):**

12

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.870 inches first hole

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Drilled hole in shank end 0.750 dia., 0.780 long. Shank surface treatment sulfamate nickel per ss8414 tyz cl1

**Material:**

Steel

**Surface Treatment:**

Cadmium headcadmium threads

**Surface Treatment Specification:**

Mil-std-865 military specification single treatment response headmil-std-865 military specification single treatment response threads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-std-865 spec.