

View Online at <https://aerobasegroup.com/nsn/5306-01-144-6271>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.753 inches and 0.803 inches

Fastener Length:

Between 1.888 inches and 1.918 inches

Head Style:

Spline extended washer

Head Height:

Between 0.310 inches and 0.350 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.053 inches and 0.073 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Head Minor Diameter:

Between 0.514 inches and 0.521 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 1.115 inches and 1.135 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, type 2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.