## NSN 5306-01-145-1194

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-145-1194

Throad Class:			
Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
Between 0.526 inches and 0.576 inches			
Fastener Length:			
Between 1.661 inches and 1.691 inches			
Head Style:			
Spline extended washer			
Head Height:			
Between 0.247 inches and 0.287 inches			
Extended Washer Diameter:			
Between 0.575 inches and 0.585 inches			
Extended Washer Thickness:			
Between 0.035 inches and 0.055 inches			
Hole Diameter:			
Between 0.050 inches and 0.060 inches			
Grip Diameter:			
Between 0.3115 inches and 0.3120 inches			
Head Minor Diameter:			
Between 0.383 inches and 0.389 inches			
Thread Diameter:			
0.312 inches			
Grip Length:			
Between 1.115 inches and 1.135 inches			
Hole Quantity:			
4			
Hole Type:			
Drilled			
Thready Qty Per Inch (tpi):			
24			
Min. Tensile Strength (psi):			
220000 pounds per square inch			
Hole Configuration Style:			
Spline			
Material:			

Material Specification:

Steel comp xm-13

Ams 5629 assn standard single material response

**Surface Treatment:** 

Passivate

## NSN 5306-01-145-1194

Shear Bolt - Page 2 of 2



Surface	<b>Treatment</b>	Specification:
---------	------------------	----------------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0