## NSN 5306-01-145-4554

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-145-4554 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.526 inches and 0.576 inches **Fastener Length:** Between 1.661 inches and 1.691 inches **Head Style:** Spline extended washer **Head Height:** Between 0.302 inches and 0.322 inches Width Between Flats: Between 0.383 inches and 0.389 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.035 inches and 0.055 inches **Shoulder Diameter:** 0.3427 inches first shoulder and 0.3432 inches first shoulder **Shoulder Length:** 1.115 inches first shoulder and 1.135 inches first shoulder **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## **NSN 5306-01-145-4554** Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A003b0