

View Online at <https://aerobasegroup.com/nsn/5306-01-147-1208>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.027 inches and 1.077 inches

Fastener Length:

Between 3.099 inches and 3.129 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.701 inches and 0.721 inches

Width Between Flats:

Between 0.803 inches and 0.814 inches

Extended Washer Diameter:

Between 1.220 inches and 1.230 inches

Extended Washer Thickness:

Between 0.168 inches and 0.188 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.7485 inches and 0.7490 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 2.052 inches and 2.072 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Material:

Steel comp xm-13

Material Specification:

23-112 type a, fscm 76301 mfr ref single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0