NSN 5306-01-147-6729

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-147-6729 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.210 inches and 0.250 inches **Fastener Length:** Between 1.070 inches and 1.100 inches **Head Style:** Hexagon **Head Height:** 0.130 inches Width Between Flats: Between 0.367 inches and 0.376 inches **First Diameter From Head:** Between 0.207 inches and 0.212 inches **Second Diameter From Head:** Between 0.147 inches and 0.153 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.360 inches and 0.370 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.850 inches and 0.860 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 33.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** Navy special project **Special Features:** Paint federal standard 595 color no. 37033 Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment:**

Paint grip

Surface Treatment Specification:

Qq-p-416, type 3 cl 2 federal specification single treatment response threads

NSN 5306-01-147-6729

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0