NSN 5306-01-147-8225

U Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-147-8225

| Thread Class: | |
|---|--|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 2.500 inches | |
| Distance From Inside Center Of Bend To Bolt End: | |
| 8.120 inches | |
| Inside Distance Between Shanks: | |
| 2.120 inches | |
| Thread Diameter: | |
| 0.500 inches | |
| Thready Qty Per Inch (tpi): | |
| 20 | |
| Material: | |
| Steel comp 1035 or steel comp 1536 or steel comp 103 | 37 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541 |
| or steel comp 1042 | |
| Surface Treatment: | |
| Paint | |
| Surface Treatment Specification: | |
| Tt-p-636 military specification single treatment response | 4 |
| Style Designator: | |
| Square bend | |
| Thread Series Designator: | |
| Unf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |
| Mil-std (military Standard): | |
| spec. | |