NSN 5306-01-147-9762

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-147-9762

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.027 inches and 1.077 inches |
| Fastener Length: |
| Between 2.599 inches and 2.629 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.701 inches and 0.721 inches |
| Width Between Flats: |
| Between 0.803 inches and 0.814 inches |
| Extended Washer Diameter: |
| Between 1.220 inches and 1.230 inches |
| Extended Washer Thickness: |
| Between 0.168 inches and 0.188 inches |
| Hole Diameter: |
| Between 0.050 inches and 0.060 inches |
| Grip Diameter: |
| Between 0.7485 inches and 0.7490 inches |
| End Application: |
| Aircraft, eagle f-15 |
| Thread Diameter: |
| 0.750 inches |
| Grip Length: |
| Between 1.552 inches and 1.572 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 16 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |

Material:

Steel comp xm-13

Material Specification:

23-112 type a, fscm 76301 mfr ref single material response

NSN 5306-01-147-9762

Shear Bolt - Page 2 of 2

Fiig: A003b0

