

View Online at <https://aerobasegroup.com/nsn/5306-01-149-4402>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.000 inches and 1.050 inches

Fastener Length:

Between 5.010 inches and 5.040 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.590 inches and 0.610 inches

Width Between Flats:

0.846 inches

Extended Washer Diameter:

Between 1.045 inches and 1.055 inches

Extended Washer Thickness:

Between 0.108 inches and 0.128 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Thread Diameter:

0.562 inches

Grip Length:

Between 3.990 inches and 4.010 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type1, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.