
## NSN 5306-01-149-4402

Shear Bolt - Page 1 of 2





### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 1.000 inches and 1.050 inches

#### Fastener Length:

Between 5.010 inches and 5.040 inches

#### Head Style:

Double hexagon w/hole

#### **Head Height:**

Between 0.590 inches and 0.610 inches

#### Width Between Flats:

0.846 inches

#### **Extended Washer Diameter:**

Between 1.045 inches and 1.055 inches

#### **Extended Washer Thickness:**

Between 0.108 inches and 0.128 inches

#### **Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

#### **Thread Diameter:**

0.562 inches

Grip Length:

Between 3.990 inches and 4.010 inches

#### Thready Qty Per Inch (tpi):

18

#### Min. Tensile Strength (psi):

260000 pounds per square inch

#### Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

#### Material:

Steel comp h11

#### Material Specification:

Ams6485 assn standard single material response or ams6487 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Mil-c-8837, type1, class 2 military specification single treatment response

#### Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-149-4402

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

