NSN 5306-01-149-6279

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-149-6279 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.547 inches and 0.688 inches **Fastener Length:** Between 0.658 inches and 0.688 inches **Head Style:** Hexagon **Head Height:** Between 0.195 inches and 0.211 inches Width Between Flats: Between 0.489 inches and 0.500 inches Washer Quantity: **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 18 **Hardness Rating:** 42.0 rockwell c primary washer and 48.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.620 inches and 0.640 inches **Primary Washer Style:** Spring tension **Primary Washer Material Thickness:** Between 0.052 inches and 0.060 inches **Special Features:** Strip locking element on thread Material: Steel primary washer **Material Specification:** Sae assn standard single material response primary washer **Surface Treatment:** Phosphate **Surface Treatment Specification:** Gm 4435-m code a mfr ref single treatment response **Thread Series Designator:** Unrc

Shelf Life:

N/a

NSN 5306-01-149-6279

Assembled Washer Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0