

View Online at <https://aerobasegroup.com/nsn/5306-01-149-6279>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.547 inches and 0.688 inches

**Fastener Length:**

Between 0.658 inches and 0.688 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.195 inches and 0.211 inches

**Width Between Flats:**

Between 0.489 inches and 0.500 inches

**Washer Quantity:**

1

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

42.0 rockwell c primary washer and 48.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.620 inches and 0.640 inches

**Primary Washer Style:**

Spring tension

**Primary Washer Material Thickness:**

Between 0.052 inches and 0.060 inches

**Special Features:**

Strip locking element on thread

**Material:**

Steel primary washer

**Material Specification:**

Sae assn standard single material response primary washer

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Gm 4435-m code a mfr ref single treatment response

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0