

View Online at <https://aerobasegroup.com/nsn/5306-01-150-1196>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.848 inches and 0.898 inches

**Fastener Length:**

Between 4.233 inches and 4.263 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.608 inches and 0.628 inches

**Width Between Flats:**

Between 0.682 inches and 0.691 inches

**Extended Washer Diameter:**

Between 1.040 inches and 1.050 inches

**Extended Washer Thickness:**

Between 0.140 inches and 0.160 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 3.365 inches and 3.385 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas630 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0