

View Online at <https://aerobasegroup.com/nsn/5306-01-150-6618>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.700 inches

Fastener Length:

11.390 inches

Head Style:

Double hexagon w/hole

Head Height:

0.250 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

0.620 inches

Point Length:

0.132 inches

First Diameter From Head:

0.300 inches

Second Diameter From Head:

Between 0.570 inches and 0.580 inches

Third Diameter From Head:

Between 0.373 inches and 0.375 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

9.230 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

9.460 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

10.426 inches

Point Style:

Cup

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Externally Relieved Body Diameter Quantity:

3

Special Features:

One hole in undercut 0.1255 in. Diameter maximum and 0.1250 in. Diameter min; 1.730 in. From head top to center of hole; spherical pad on shoulder 0.370 in. Diameter min and 0.372 in diameter maximum 0.630 in. From head top to middle of spher; three holes in the head 0.046 in. Diameter min and 0.056 in. Diameter max

Material:

Steel

Material Specification:

Ams 6411 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0