

View Online at <https://aerobasegroup.com/nsn/5306-01-150-9497>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.585 inches and 0.615 inches

Fastener Length:

Between 1.970 inches and 2.000 inches

Head Style:

Hexagon

Head Height:

Between 0.195 inches and 0.211 inches

Width Between Flats:

Between 0.489 inches and 0.500 inches

Shoulder Diameter:

0.380 inches first shoulder and 0.385 inches first shoulder

Shoulder Length:

1.310 inches first shoulder

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

74000 pounds per square inch

Hardness Rating:

80.0 rockwell b and 100.0 rockwell b

Shoulder Shape:

Round first shoulder

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0