

View Online at <https://aerobasegroup.com/nsn/5306-01-151-4127>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.516 inches and 0.566 inches

Fastener Length:

Between 4.276 inches and 4.306 inches

Head Style:

Dished hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 3.740 inches and 3.760 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 1 class 3 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1110 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0