## NSN 5306-01-152-4934

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-152-4934 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.579 inches **Fastener Length:** 3.099 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.348 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** 0.082 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.3125 inches **Grip Length:** 

Between 2.399 inches and 2.601 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

**Hardness Rating:** 

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

**Material Specification:** 

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416 type ii class 2 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-01-152-4934

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.