

View Online at <https://aerobasegroup.com/nsn/5306-01-153-1370>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.506 inches and 0.650 inches

Fastener Length:

Between 5.204 inches and 5.328 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.679 inches and 0.690 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Thread Diameter:

0.437 inches

Grip Length:

Between 4.678 inches and 4.698 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 or steel comp 8740 or steel comp 4140 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 1 class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1307 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0