## NSN 5306-01-153-1370

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-153-1370

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.506 inches and 0.650 inches
Fastener Length:
Between 5.204 inches and 5.328 inches
Head Style:
Dished hexagon
Head Height:
Between 0.219 inches and 0.234 inches
Width Between Flats:
Between 0.679 inches and 0.690 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Thread Diameter:
0.437 inches
Grip Length:
Between 4.678 inches and 4.698 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
63.0 microinches grip
Material:
Steel comp e4340 or steel comp 8740 or steel comp 4140 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type 1 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1307 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5306-01-153-1370

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0