## NSN 5306-01-155-8651

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-155-8651

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.506 inches and 0.650 inches **Fastener Length:** Between 5.204 inches and 5.328 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 4.678 inches and 4.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 63.0 microinches grip Material: Steel comp e4340 or steel comp 8740 or steel comp 4140 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 1 class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1306 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

## NSN 5306-01-155-8651

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0