

View Online at <https://aerobasegroup.com/nsn/5306-01-155-9767>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.875 inches and 1.937 inches

Fastener Length:

Between 10.000 inches and 10.062 inches

Head Style:

Hexagon

Head Height:

0.609 inches

Width Between Flats:

1.500 inches

End Application:

Nsn 2320-01-097-0260 hemtt (heavy expanded mobility tactical truck)

Thread Diameter:

1.000 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1524 or steel comp 1527 or steel comp 1536 or steel comp 1541

Material Specification:

Sae j429 assn standard single material response

Surface Treatment:

Phosphate

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0