

View Online at <https://aerobasegroup.com/nsn/5306-01-156-5432>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.475 inches

**Fastener Length:**

3.840 inches

**Head Style:**

Round w/wrench flats chamfered

**Head Diameter:**

1.125 inches

**Head Height:**

0.190 inches

**Width Between Flats:**

0.875 inches

**Shoulder Diameter:**

0.7475 inches first shoulder and 0.7490 inches first shoulder

**Shoulder Length:**

4.030 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.140 inches first hole and 0.150 inches first hole

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

280000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.640 inches first hole

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Longitudinal hole through full length of item; dia. 0.328 in.

**Material:**

Steel

**Material Specification:**

Mil-s-8844 cl 3 cond e2 military specification single material response

**Surface Treatment:**

Chromium grip

**Surface Treatment Specification:**

Stf1181, fscm 76301 mfr ref single treatment response threads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-8844 spec.