

View Online at <https://aerobasegroup.com/nsn/5306-01-156-5432>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.475 inches

Fastener Length:

3.840 inches

Head Style:

Round w/wrench flats chamfered

Head Diameter:

1.125 inches

Head Height:

0.190 inches

Width Between Flats:

0.875 inches

Shoulder Diameter:

0.7475 inches first shoulder and 0.7490 inches first shoulder

Shoulder Length:

4.030 inches first shoulder

Shank Unthreaded Hole Diameter:

0.140 inches first hole and 0.150 inches first hole

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

280000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.640 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Longitudinal hole through full length of item; dia. 0.328 in.

Material:

Steel

Material Specification:

Mil-s-8844 cl 3 cond e2 military specification single material response

Surface Treatment:

Chromium grip

Surface Treatment Specification:

Stf1181, fscm 76301 mfr ref single treatment response threads

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8844 spec.