## NSN 5306-01-156-5433

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-156-5433

View Online at https://aerobasegroup.com/nsn/5306-01-156-5433
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.395 inches and 0.486 inches
Fastener Length:
Between 0.748 inches and 0.788 inches
Head Style:
Hexagon
Head Height:
Between 0.203 inches and 0.235 inches
Width Between Flats:
Between 0.553 inches and 0.565 inches
Shoulder Diameter:
0.371 inches first shoulder and 0.374 inches first shoulder
Shoulder Length:
0.260 inches first shoulder and 0.270 inches first shoulder
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Unjf
Unjf Specification Data:
Unif  Specification Data:  80205-nas1297 professional/industrial association standard
Unif  Specification Data:  80205-nas1297 professional/industrial association standard  Shelf Life:

--

## **NSN 5306-01-156-5433** Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0