

View Online at <https://aerobasegroup.com/nsn/5306-01-156-5435>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.658 inches and 0.750 inches

Fastener Length:

Between 0.720 inches and 0.750 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.304 inches and 0.330 inches

Width Between Flats:

Between 0.551 inches and 0.562 inches

Extended Washer Diameter:

Between 0.771 inches and 0.793 inches

Extended Washer Thickness:

Between 0.070 inches and 0.096 inches

Locking Feature:

Locking teeth bearing surface of head

Thread Diameter:

0.375 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

16

Hardness Rating:

22.0 rockwell c and 35.0 rockwell c

Special Features:

24 serrations in locking head

Material:

Steel comp 1018 or steel comp 1021 or steel comp 1022

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Zinc

Surface Treatment Specification:

Gm 4342-m, code20u32 fscm 11862 mfr ref single treatment response

Thread Series Designator:

Unrc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0