

View Online at <https://aerobasegroup.com/nsn/5306-01-156-5435>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.658 inches and 0.750 inches

**Fastener Length:**

Between 0.720 inches and 0.750 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

Between 0.304 inches and 0.330 inches

**Width Between Flats:**

Between 0.551 inches and 0.562 inches

**Extended Washer Diameter:**

Between 0.771 inches and 0.793 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.096 inches

**Locking Feature:**

Locking teeth bearing surface of head

**Thread Diameter:**

0.375 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

16

**Hardness Rating:**

22.0 rockwell c and 35.0 rockwell c

**Special Features:**

24 serrations in locking head

**Material:**

Steel comp 1018 or steel comp 1021 or steel comp 1022

**Material Specification:**

Sae assn standard all material responses

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Gm 4342-m, code20u32 fscm 11862 mfr ref single treatment response

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0