NSN 5306-01-156-5436

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-156-5436

Thread Direction: Right-hand Thread Length: Between 0.318 inches and 0.438 inches Fastener Length: Between 0.407 inches and 0.438 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	
Thread Direction: Right-hand Thread Length: Between 0.318 inches and 0.438 inches Fastener Length: Between 0.407 inches and 0.438 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Thread Class:
Right-hand Thread Length: Between 0.318 inches and 0.438 inches Fastener Length: Between 0.407 inches and 0.438 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	2a
Thread Length: Between 0.318 inches and 0.438 inches Fastener Length: Between 0.407 inches and 0.438 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Thread Direction:
Between 0.318 inches and 0.438 inches Fastener Length: Between 0.407 inches and 0.438 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Right-hand
Fastener Length: Between 0.407 inches and 0.438 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Thread Length:
Between 0.407 inches and 0.438 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Between 0.318 inches and 0.438 inches
Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Fastener Length:
Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Between 0.407 inches and 0.438 inches
Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Head Style:
Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Hexagon
Width Between Flats: Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Head Height:
Between 0.428 inches and 0.438 inches Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Between 0.150 inches and 0.163 inches
Locking Feature: Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Width Between Flats:
Patch threads or strip threads Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Between 0.428 inches and 0.438 inches
Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Locking Feature:
Co. 250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Patch threads or strip threads
Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Thread Diameter:
Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	0.250 inches
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Features Provided:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Finished head
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Thready Qty Per Inch (tpi):
150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	28
Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Min. Tensile Strength (psi):
Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	150000 pounds per square inch
Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Hardness Rating:
Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	32.0 rockwell c fastener and 38.0 rockwell c fastener
Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Material:
Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Steel fastener
Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Material Specification:
Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Sae j429 grade 8 assn standard single material response fastener
Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Surface Treatment:
Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Zinc fastener and chromate fastener
Thread Series Designator: Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Surface Treatment Specification:
Unf Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Astm b633 type 2 sc 3 assn standard single treatment response fastener
Specification Or Standard: 2 type and 10p style and 8 grade Shelf Life: N/a	Thread Series Designator:
2 type and 10p style and 8 grade Shelf Life: N/a	Unf
Shelf Life: N/a	Specification Or Standard:
N/a	2 type and 10p style and 8 grade
	Shelf Life:
Unit Of Maggura	N/a
Offic Of Wedsure.	Unit Of Measure:

--

NSN 5306-01-156-5436

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0