## NSN 5306-01-156-5439

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-156-5439



## Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.589 inches and 0.639 inches

#### Fastener Length:

Between 2.911 inches and 2.941 inches

#### Head Style:

Spline extended washer

## Head Height:

Between 0.263 inches and 0.303 inches

## **Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

## **Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

## Hole Diameter:

Between 0.050 inches and 0.060 inches

## Grip Diameter:

Between 0.3740 inches and 0.3745 inches

## Head Minor Diameter:

Between 0.448 inches and 0.455 inches

## Thread Diameter:

0.375 inches

## Grip Length:

Between 2.302 inches and 2.322 inches

## Hole Quantity:

4

Hole Type:

Drilled

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

220000 pounds per square inch

## Hole Configuration Style:

Spline

## Product Name:

Navy special project

Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

# NSN 5306-01-156-5439

Shear Bolt - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0