

View Online at <https://aerobasegroup.com/nsn/5306-01-156-9455>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 22.0 millimeters and 23.0 millimeters

**Fastener Length:**

Between 162.20 millimeters and 162.80 millimeters

**Head Style:**

Spline extended washer

**Head Height:**

Between 8.2 millimeters and 9.0 millimeters

**Extended Washer Diameter:**

Between 20.4 millimeters and 21.5 millimeters

**Extended Washer Thickness:**

Between 2.9 millimeters and 3.2 millimeters

**Grip Diameter:**

Between 11.9590 millimeters and 11.9840 millimeters

**Thread Diameter:**

12.0 millimeters

**Grip Length:**

Between 139.80 millimeters and 140.20 millimeters

**Min. Tensile Strength (psi):**

1250 megapascals

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Thread Pitch In Millimeters:**

1.25

**Surface Finish:**

0.8 micrometers threads

**Material:**

Steel comp e4340 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0058 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0