NSN 5306-01-157-3372

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-157-3372

View Online at https://aerobasegroup.com/nsn/5306-01-157-3372			
Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
Between 0.589 inches and 0.639 inches			
Fastener Length:			
Between 1.724 inches and 1.754 inches			
Head Style:			
Spline extended washer			
Head Height:			
Between 0.263 inches and 0.303 inches			
Extended Washer Diameter:			
Between 0.691 inches and 0.701 inches			
Extended Washer Thickness:			
Between 0.044 inches and 0.064 inches			
Grip Diameter:			
Between 0.3735 inches and 0.3745 inches			
Head Minor Diameter:			
Between 0.424 inches and 0.438 inches			
Thread Diameter:			
0.375 inches			
Grip Length:			
Between 1.115 inches and 1.135 inches			
Thready Qty Per Inch (tpi):			
24			
Min. Tensile Strength (psi):			
220000 pounds per square inch			
Hardness Rating:			
36.0 rockwell c and 40.0 rockwell c			
Material:			
Steel comp xm-13			
Material Specification:			
Ams5629 assn standard single material response			
Surface Treatment:			
Aluminum and chromate			
Surface Treatment Specification:			
Mil-c-83488, type 2 cl 3 military specification single treatment response			
Thread Series Designator:			
Unjf			
Shelf Life:			
N/a			

NSN 5306-01-157-3372

Shear Bolt - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.