## NSN 5306-01-157-3372

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-157-3372

View Online at https://aerobasegroup.com/nsn/5306-01-157-3372				
Thread Class:				
3a				
Thread Direction:				
Right-hand				
Thread Length:				
Between 0.589 inches and 0.639 inches				
Fastener Length:				
Between 1.724 inches and 1.754 inches				
Head Style:				
Spline extended washer				
Head Height:				
Between 0.263 inches and 0.303 inches				
Extended Washer Diameter:				
Between 0.691 inches and 0.701 inches				
Extended Washer Thickness:				
Between 0.044 inches and 0.064 inches				
Grip Diameter:				
Between 0.3735 inches and 0.3745 inches				
Head Minor Diameter:				
Between 0.424 inches and 0.438 inches				
Thread Diameter:				
0.375 inches				
Grip Length:				
Between 1.115 inches and 1.135 inches				
Thready Qty Per Inch (tpi):				
24				
Min. Tensile Strength (psi):				
220000 pounds per square inch				
Hardness Rating:				
36.0 rockwell c and 40.0 rockwell c				
Material:				
Steel comp xm-13				
Material Specification:				
Ams5629 assn standard single material response				
Surface Treatment:				
Aluminum and chromate				
Surface Treatment Specification:				
Mil-c-83488, type 2 cl 3 military specification single treatment response				
Thread Series Designator:				
Unjf				
Shelf Life:				
N/a				

## NSN 5306-01-157-3372

Shear Bolt - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.