

View Online at <https://aerobasegroup.com/nsn/5306-01-157-6797>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.301 inches and 0.404 inches

**Fastener Length:**

Between 0.470 inches and 0.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.190 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**Washer Quantity:**

1

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

40.0 rockwell c primary washer and 48.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.743 inches and 0.765 inches

**Primary Washer Style:**

Spring tension

**Primary Washer Material Thickness:**

Between 0.074 inches and 0.087 inches

**Material:**

Steel

**Material Specification:**

Sae assn standard all material responses primary washer

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

G-6111- (400) , fscm 11862 mfr ref single treatment response

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0