

View Online at <https://aerobasegroup.com/nsn/5306-01-158-6243>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.971 inches and 1.093 inches

Fastener Length:

Between 1.531 inches and 1.563 inches

Head Style:

Spline extended washer

Head Diameter:

Between 0.610 inches and 0.640 inches

Head Height:

0.220 inches

Distance From Centerline To Flat:

0.200 inches

Rib Major Diameter:

Between 0.385 inches and 0.389 inches

Rib Length:

0.160 inches

Rib Minor Diameter:

Between 0.356 inches and 0.366 inches

Rib Quantity:

36

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Material:

Steel comp 1013

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Phosphate

Surface Treatment Specification:

G-4435-m code a fscm 11862 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0