## NSN 5306-01-160-0772

Shear Bolt - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.413 inches and 0.463 inches

## Fastener Length:

Between 1.735 inches and 1.765 inches

#### **Head Style:**

Dished hexagon

## Head Height:

Between 0.156 inches and 0.171 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.3110 inches and 0.3120 inches

## **Thread Diameter:**

0.312 inches

## Grip Length:

Between 1.302 inches and 1.322 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Surface Finish:

32.0 microinches threads

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

## **Thread Series Designator:**

Unf

## Specification Data:

80205-nas6305 professional/industrial association standard

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-160-0772

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

