NSN 5306-01-160-1948

Machine Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-160-1948

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.865 inches and 0.945 inches |
| Fastener Length: |
| Between 2.115 inches and 2.135 inches |
| Head Style: |
| Double hexagon extended washer |
| Head Height: |
| Between 0.328 inches and 0.348 inches |
| Width Between Flats: |
| 0.375 inches |
| Extended Washer Diameter: |
| Between 0.490 inches and 0.510 inches |
| Extended Washer Thickness: |
| Between 0.070 inches and 0.080 inches |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 1.190 inches and 1.250 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 24 |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| C50tf13 cl-b fscm 07482 mfr ref single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |